



XF-PTL05532-F-VI

Optional camera mount:
 1、F
 2、M42×1

Specification

Optical structure	Bi-Telecentric
Magnification	0.597
Object field of view	$\phi 53.6\text{mm}$
Image field of view	$\phi 32\text{mm}$
Working Distance	$138\text{mm} \pm 3\%$
Telecentricity	$< 0.04^\circ (0.06^\circ)$
Depth of field	1.9-13.2mm
F#	F7.5-F42.2
Resolution	$8.3-46.7\mu\text{m}$
MTF	$> 0.3 @ 135-25\text{lp/mm}$
Distortion	$< 0.060\% (0.1\%)$
Detector type:	

7/4' 22.5×16.9	37.7×28.3mm
4/3' 18×13.5	30.2×22.6mm
1.1' 14.2×10.4	23.8×17.4mm
1' 12.8×9.6	21.4×16.1mm
2K Linear scan 2048×10 μm	34.3mm
4K Linear scan 4096×7 μm	48.0mm

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV</p> <p>Image FOV</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p>90° Steering option</p>	
--	---	--

Undefined tolerance (mm)	degree	File Name			
X. X	± 0.2	$\pm 30\text{min}$	XF-PTL05532-F-VI-外形尺寸-EN		
X. XX	± 0.02	Drawing Name			
X. XXX	± 0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.