



XF-PTL15229-F

Optional camera mount
 1、 F
 2、 M42×1

Specification

Optical structure	Bi-Telecentric
Magnification	0.192
Object field of view	Φ151.0mm
Image field of view	Φ29mm
Working Distance	320mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	20.9mm
F#	F7
Resolution	24.1μm
MTF	>0.3@145lp/mm
Distortion	<0.042%(0.072%)
Detector type:	

7/4' 22.5×16.9	117.2×88.0mm
4/3' 18.0×13.5	93.8×70.3mm
1.1' 14.2×10.4	74.0×54.2mm
1' 12.8×9.6	66.7×50.0mm
2K Linear scan 2048×10μm	106.7mm
4K Linear scan 4096×7μm	146.3mm

XF-PTLAAABB-C/F/P/M- (L90E)

The fourth generation lens of Canrill	The camera mount (M & P mount need specify BFL)
Object FOV	90° Steering option
Image FOV	

Undefined tolerance (mm)	degree	File Name		
X. X	±0.2	±30min	XF-PTL15229-F-外形尺寸-EN	
X. XX	±0.02	Drawing Name		
X. XXX	±0.005	Drawing Size: A3		
	Sign	Data/Ver.	Material	Ratio
Design				1:5
Modify1			Qty	☐ ⊕
Modify2			Total:	Page: