



## XF-PTL15232-F

**Optional camera mount**  
 1、 F  
 2、 M42×1

### Specification

Optical structure	Bi-Telecentric
Magnification	0.217
Object field of view	Φ147.5mm
Image field of view	Φ32mm
Working Distance	320mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	17.7mm
F#	F7.5
Resolution	22.85μm
MTF	>0.3@135lp/mm
Distortion	<0.053%(0.072%)
Detector type:	

7/4'	22.6×16.9	103.7×77.9mm
4/3'	18×13.5	82.9×62.2mm
1.1'	14.2×10.4	65.4×47.9mm
1'	12.8×9.6	59.0×44.2mm
2K Linear scan	2048×10μm	94.4mm
4K Linear scan	4096×7μm	132.1mm

**XF-PTLAAABB-C/F/P/M- (L90E)**

<p><b>The fourth generation lens of Canrill</b></p> <p>Object FOV _____</p> <p>Image FOV _____</p>	<p><b>The camera mount (M &amp; P mount need specify BFL)</b></p> <p style="text-align: right;"><b>90° Steering option</b></p>
--	--

Undefined tolerance (mm)		degree	File Name		
X. X	±0.2	±30min	XF-PTL15232-F-外形尺寸-EN		
X. XX	±0.02		Drawing Name		
X. XXX	±0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.